



Technical Data Sheet

MACSEAL-AQ Water Based Cure & Seal

Revision
June 2023

See your MAC Coatings distributor for specific performance characteristics or requirements.

Description

A clear, soft gloss, quick drying cure and seal compound designed to provide a premium seal on freshly poured concrete. The primary function of MACSEAL-AQ is moisture retention and should be applied in any situation where simultaneous curing and sealing is desired. Can also be used as a concrete sealer on old concrete when a soft gloss finish is desired. When properly applied, this compound reduces the common defects that result from a concrete that has not been properly cured such as dusting and premature cracking. Provides concrete with protection during construction.

Limitations

For curing purposes on freshly poured concrete, compound must be applied once all surface water has evaporated, and the concrete will not be marred by walking traffic.

For sealing purposes on existing concrete, surface must be dry as moisture will adversely affect the clarity of the sealer. Multiple coats may yield a surface which is slippery.

Surface Preparation

Cement must be dry and free of oil and contaminants. Oily patches can be treated with xylene or a surface cleaner. Sweep or blow all debris from area to be sealed.

Application

Ready to use with roller or spray. Product does not require reduction. Clean up tools with soap and water. Roll or spray a full wet coat but do not allow products to puddle in low spots. Material can be top coated if desired as soon as previous coat is dry to touch.

The ratings and data contained herein are based on information obtained through experimental laboratory methods. They are offered in good faith, however without guarantee to individual results, as the customer's applications, requirements; conditions and methods of use are beyond our control. We recommend that the customer determine the suitability of these materials before adopting them for its own use.

P: (519) 252-7275 F: (519) 252-7278 1106 Walker Rd, Windsor, ON N8Y2N7



Technical Data Sheet

Physical Properties

NOTE: All specification data is represented as general laboratory or production results and does not necessarily constitute a specification. Values not represented as ranges are intended as typical.

Caution

Use in well-ventilated areas, keep out of reach of children.

Technical Data

Colour	: Clear
Sheen	: Soft Gloss
Cure Type	: Evaporation, Oxidation
Dry Time	: 30 minutes at 21°C 50%RH
Theoretical Coverage	: 280 ft ² per USG
Solids By Weight	: 18%

The ratings and data contained herein are based on information obtained through experimental laboratory methods. They are offered in good faith, however without guarantee to individual results, as the customer's applications, requirements; conditions and methods of use are beyond our control. We recommend that the customer determine the suitability of these materials before adopting them for its own use.