



Technical Data Sheet

SPRAYSEAL Acrylic Sealer

Revision
June 2023

See your MAC Coatings distributor for specific performance characteristics or requirements.

Description

A clear quick drying sealer available in natural, semi, and high gloss forms. It was designed with the contractor in mind to protect stamped concrete, paving blocks, poured concrete, interlocking stone, and exposed aggregate from weathering and traffic.

The product is ready to use by spray, enabling users to work quickly and efficiently. While remaining very economical, SPRAYSEAL contains a synergistic ultraviolet inhibitor system which greatly increase the life of the coating. This product complies with current Canadian maximum VOC content limit of 400g/L concrete sealing compounds.

SPRAYSEAL can be adjusted for a low, high, or semi-gloss.

Limitations

For curing purposes on freshly poured concrete, compound must be applied once all surface water has evaporated, and the concrete will not be marred by walking traffic.

For sealing purposes on existing concrete, surface must be dry as moisture will adversely affect the clarity of the sealer. Multiple coats may yield a surface which is slippery.

Surface Preparation

Cement must be dry and free of oil and contaminants. Oily patches can be treated with xylene or a surface cleaner. Sweep or blow all debris from area to be sealed.

Application

Ready to use with roller or spray. Product does not require reduction. Clean up tools with xylene. Roll or spray a full wet coat but do not allow products to puddle in low spots. Material can be top coated, if desired as soon as previous coat is dry to touch.

The ratings and data contained herein are based on information obtained through experimental laboratory methods. They are offered in good faith, however without guarantee to individual results, as the customer's applications, requirements; conditions and methods of use are beyond our control. We recommend that the customer determine the suitability of these materials before adopting them for its own use.



Technical Data Sheet

Physical Properties

NOTE: All specification data is represented as general laboratory or production results and does not necessarily constitute a specification. Values not represented as ranges are intended as typical.

Caution

Use in well-ventilated areas, keep out of reach of children.

Technical Data

Generic Type	: Acrylic
Colour	: Clear
Sheen	: Low, high, or semi-Gloss
Cure Type	: Evaporation, Oxidation
Dry Time	: 20 mins at 21°C 50% RH
Theoretical Coverage	: 280 ft ² per USG
Solids By Weight	: 12%-25%

The ratings and data contained herein are based on information obtained through experimental laboratory methods. They are offered in good faith, however without guarantee to individual results, as the customer's applications, requirements; conditions and methods of use are beyond our control. We recommend that the customer determine the suitability of these materials before adopting them for its own use.