



Technical Data Sheet

MAC Thread Spray Alkyd Enamel

Revision
May 2023

See your MAC Coatings distributor for specific performance characteristics or requirements.

Description

A high performance quick dry enamel designed for use as a single coat applied directly to metal substrates. Product will dry to a durable hardshell film that exhibits excellent corrosion resistance and hardness.

Application

Ready to use. Product does not require reduction.

Physical Properties

NOTE: All specification data is represented as general laboratory or production results and does not necessarily constitute a specification. Values not represented as ranges are intended as typical.

Color	: Various
Odor	: Solvent Like
lbs per USG	: 8.0 – 8.5 (typical)
Solids by wt	: 45% (typical)
:	

Caution

Use in well-ventilated areas, keep out of reach of children.

The ratings and data contained herein are based on information obtained through experimental laboratory methods. They are offered in good faith, however without guarantee to individual results, as the customer's applications, requirements; conditions and methods of use are beyond our control. We recommend that the customer determine the suitability of these materials before adopting them for its own use.

P: (519) 252-7275 F: (519) 252-7278 1106 Walker Rd, Windsor, ON N8Y2N7



Technical Data Sheet

Generic Type	: Solvent Based Alkyd
Color	: Various
Gloss	: Low
Cure Type	Oxidation;
Cure time	Finger dry: 25 min Dry hard: 30-45 min
Reducer	Xylene

Technical Data

--	--

The ratings and data contained herein are based on information obtained through experimental laboratory methods. They are offered in good faith, however without guarantee to individual results, as the customer's applications, requirements; conditions and methods of use are beyond our control. We recommend that the customer determine the suitability of these materials before adopting them for its own use.