SDS Revision Date: 01/18/2023



1. Identification

1.1. Product identifier

Product Identity SOL-1003

Alternate Names Naphtha, Stoddard solvent, White Spirit

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended useSee Technical Data Sheet.Application MethodSee Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Mac Coatings

1106 WALKER ROAD WINDSOR, ONTARIO

N8Y 2N7

Customer Service: Mac Coatings (519)-252-7275

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 3; H226 Flammable liquid and vapor.

Skin irrit. 2; H315 Causes skin irritation. Eye irrit. 2B; H320 Causes eye irritation.

STOT SE 3; H336 May cause drowsiness or dizziness.

Asp. haz. 1; H304 May be fatal if swallowed and enters airways.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



DANGER

SDS Revision Date: 01/18/2023



H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H320 Causes eye irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

[Prevention]:

P210+ 260 Keep away from heat / sparks / open flames / hot surfaces - No smoking. Do not breath dust/fume/gas/mist/vapors/spray

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection. Use only outdoors or in a well ventilated area.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 **IF ON SKIN (or hair):** Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P340 IF INHAILED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P304+312 **IF INHALED**: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P301+ 310 If swallowed: immediately call a poison center or a doctor. DO NOT INDUCE VOMITING.

P332+313 If skin irritation occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P362 Take off contaminated clothing and wash before reuse.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

2.3. Other Hazards

Vapors can accumulate in low areas.

SDS Revision Date: 01/18/2023



3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Stoddard solvent CAS Number: 0008052-41-3	100	Flam. Liq. 3; H226 Skin irrit. 2; H315 Eye irrit. 2B; H320 STOT SE 3;H336 Asp. Tox. 1;H304	[1][2]

^[1] Substance classified with a health or environmental hazard.

4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. Get Medical attention immediately.

Eyes Check for and remove any contact lenses. Immediately flush eyes with plenty of water for

at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention

immediately.

Skin In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash before reuse.

Ingestion DO NOT INDUCE VOMITING. If conscious, rinse out mouth with water.

4.2. Most important symptoms and effects, both acute and delayed

Overview Effects of overexposure:

Acute: Eyes-may cause severe irritation, redness, tearing, blurred vision.

Skin/skin absorption- Prolonged or repeated contact can cause moderate irritation.

Defatting, dermatitis.

Breathing-excessive inhalation of vapors can cause nasal and Respiratory irritation and central nervous system effects including: Dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

Swallowing-can cause gastrointestinal, irritation, nausea, vomiting, and diarrhea. Aspiration

of material into the lungs can cause chemical pneumonitis which can be fatal.

Exposure to solvent vapor concentrations in excess of the stated occupational exposure

^[2] Substance with a workplace exposure limit.

^[3] PBT-substance or vPvB-substance.

^{*}The full texts of the phrases are shown in Section 16.

SDS Revision Date: 01/18/2023



limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness

and in extreme cases, loss of consciousness.

Inhalation May cause drowsiness or dizziness. May cause irritation of the mouth. Throat or

esophagus.

Eyes Causes eye irritation. May cause stinging/watering/redness/swelling.

Skin Causes skin irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical alcohol Foam, Water fog, Carbon Dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Burning may produce irritating Or toxic fumes. Carbon dioxide and carbon monoxide, various hydrocarbons, etc.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

Evacuate hazard area. Wear self-contained breathing apparatus with a full face piece

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near container (even empty) because product (even just residue) can ignite explosively. All five gallon pails and large metal containers should be grounded and/or bonded when material is transferred.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

SDS Revision Date: 01/18/2023



Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways. Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Contain spillage and then collect with electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks, and open flames. Protect container from physical damage. Keep the container tightly closed when not in use. Store in a cool and well-Ventilated area. See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0008052-41-3	Stoddard solvent	OSHA TWA 500 ppm (2900 mg/m³)	
		ACGIH	TWA: 290 mg/m ³ STEL: 580 mg/m ³
		NIOSH	TWA 350 mg/m³ C 1800 mg/m³ [15-minute]
		Supplier	No Established Limit

8.2. Exposure controls

RespiratoryUse a properly fitted, air-purifying or air-fed respirator complying with an approved standard

if a risk assessment indicated this is necessary.

Eyes Chemical goggles and face shield.

SDS Revision Date: 01/18/2023



Skin Chemical resistant, impervious gloves complying with an approved standard should be

worn at all times. Coveralls, apron, and boots as necessary to minimize contact.

engineering controls to keep worker exposure to airborne contaminants below any

recommended or statutory limits.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance Clear, colorless liquid

Odor Mineral Spirits odor

Odor threshold Not Measured

pH Not Measured

Melting point / freezing point Not Measured

Initial boiling point and boiling range 150 - 205°C

Flash Point Closed cup 42°C

Evaporation rate (N-Butyl Acetate = 1) (X) Slower Than N-BUTYL ACETATE

Flammability (solid, gas) Flammable liquid

Upper/lower flammability or explosive limits Lower Explosive Limit: 1.0%

Upper Explosive Limit: 6.0%

Vapor pressure (hPa) Not Measured

Vapor Density (X)Heavier Than Air ()Lighter than Air

Specific Gravity 1.00

Solubility in Water immiscible

Partition coefficient n-octanol/water (Log Kow)

Not Measured

Not Measured

Decomposition temperature Not Measured

Viscosity (cSt)

Not Measured

Percent Volatile (by volume) 100

9.2. Other information

No other relevant information.

10. Stability and reactivity

SDS Revision Date: 01/18/2023



10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

Vapors may form an explosive mixture with air.

10.4. Conditions to avoid

High temperatures, flames, sparks

10.5. Incompatible materials

Avoid contact with: Strong acids and oxidizing materials.

10.6. Hazardous decomposition products

Smoke, carbon monoxide, carbon dioxide.

11. Toxicological information

Acute toxicity

Respiratory irritation

An inhalation hazard may only arise if product is used in aerosol conditions if heated up. The material is misted or if the vapors are generated from heating. Exposure may cause irritation of mucous membranes and upper respiratory tract.

Eye irritation

Causes serious eye irritation.

Skin Irritation

Causes mild skin irritation

Sensitization

Not expected to cause skin or respiratory sensitization.

Aspiration Hazard

If swallowed can be aspirated into lungs and cause chemical pneumonia, varying degrees of pulmonary injury or death.

If swallowed, do not induce vomiting.

Chronic Exposure

Vapor/aerosol concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects including death.

SDS Revision Date: 01/18/2023



Prolonged or repeated direct exposure to the skin results in symptoms of irritation and redness, dermatitis or oil acne.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Stoddard solvent - (8052-41-3)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.50, Rat - Category: NA	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value	
0008052-41-3	Stoddard solvent	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Eye damage/irritation	2B	Causes eye irritation.
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure		Not Applicable
Aspiration hazard	1	May be fatal if swallowed and enters airways.

SDS Revision Date: 01/18/2023

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish,	48 hr EC50 Crustacia,	ErC50 algae,	
	mg/l	mg/l	mg/l	
Stoddard solvent - (8052-41-3)	Not Available	Not Available	Not Available	

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No bioaccumulation is to be expected.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

DOT (Domestic Surface

14. Transport information

IMO / IMDG (Ocean

ICAO/IATA

Transportation)
Transportation)

14.1. UN number
UN1268
UN1268
UN1268
UN1268
UN1268
Petroleum distillates, (Naphtha Solvent)
(Naphtha Solvent)

SDS Revision Date: 01/18/2023



14.3. Transport hazard DOT Hazard Class: 3 IMDG: 3 Air Class: 3

class(es) Sub Class: Not Applicable

14.4. Packing group ||| ||| |||

14.5. Environmental hazards

IMDG No further information

14.6. Special precautions for user

No further information

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory.

US EPA Tier II Hazards Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes
Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (lbs):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Mineral Spirits

Pennsylvania RTK Substances (>1%):

SDS Revision Date: 01/18/2023



Mineral Spirits

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

The information contained herein is furnished without warranty of any kind. The above information is believed to be correct but does not purport to be all inclusive and should be used only as a guide. Users should make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.

End of Document