

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



1. Identification

1.1. Product identifier

Product Identity	MAC BLACK
Alternate Names	Asphalt Sealer CSS-4875-# CSS-4876-# MX-875 Asphalt Cutback

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use	See Technical Data Sheet.
Application Method	See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name	Mac Coatings 1106 WALKER ROAD WINDSOR, ONTARIO N8Y 2N7
Customer Service: Mac Coatings	(519)-252-7275

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226	Flammable liquid and vapor.
Skin Irrit. 2;H315	Causes skin irritation.
Eye Irrit. 2;H319	Causes serious eye irritation.
STOT SE 3;H335	May cause respiratory irritation.
STOT SE 3;H336	May cause drowsiness or dizziness.
Carc. 1A; H350	May Cause cancer.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



Danger

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness and dizziness.

H350 May Cause cancer.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P321 Specific treatment (see information on this label).

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



P332+313 If skin irritation occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P362 Take off contaminated clothing and wash before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

P391 Collect spillage.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Asphalt (petroleum) CAS Number: 0008052-42-4	45-55	Carc. 2; H352	[1][2]
Stoddard solvent CAS Number: 0008052-41-3	45-50	STOT RE 1;H372 Asp. Tox. 1;H304	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



Skin If hot material strikes the skin, immediately drench or immerse in cool water. Do not attempt to remove asphalt from burn after it has cooled, seek immediate medical attention. In non-burn situations wash with baby oil and/or mild non-abrasive soap for at least 15 minutes. Use warm water. Remove contaminated clothing and discard. If the irritation persists repeat the washing procedure. Seek medical attention

Ingestion DO NOT INDUCE VOMITING. This material is not soluble. DO NOT GIVE FLUIDS. If spontaneous vomiting is inevitable, PREVENT ASPIRATION by keeping the victim's head below the knees. CONTACT A PHYSICIAN IMMEDIATELY.

4.2. Most important symptoms and effects, both acute and delayed

Overview

Effects of overexposure:

Acute: Eyes-may cause severe irritation, redness, tearing, blurred vision.

Skin/skin absorption- Prolonged or repeated contact can cause moderate irritation.

Defatting, dermatitis.

Breathing-excessive inhalation of vapors can cause nasal and Respiratory irritation and central nervous system effects including: Dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

Swallowing-can cause gastrointestinal, irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation

May cause drowsiness or dizziness. May cause respiratory irritation.

Eyes

Causes serious eye irritation.

Skin

Causes skin irritation.

5. Fire-fighting measures

5.1. Extinguishing media

Class "B" dry chemical, carbon dioxide, or other suitable extinguishing material such as dry sand. Do not use halogenated agents. When flames have been eliminated, cover residue with dry extinguishing agent or dry sand and allow it to remain undisturbed until it has cooled. If fire appears to increase in intensity, stop using these agents. Apply Class "D" extinguishing agent or more dry, inert, granular material. Ring fire with extinguishing material and allow the fire to burn out.

5.2. Special hazards arising from the substance or mixture

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



Hazardous decomposition: Burning may produce irritating Or toxic fumes. Carbon dioxide and carbon monoxide, various hydrocarbons, etc.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Wear self-contained breathing apparatus with a full facepiece

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near container (even empty) because product (even just residue) can ignite explosively. All five gallon pails and large metal containers should be grounded and/or bonded when material is transferred.

ERG Guide No. 127

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Steps to be taken in case material is released or spilled: Eliminate all ignition sources (flares, flames including pilot Lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed, stop spil at source, dike area of spill to prevent spreading, pump liquid to salvage tank.

Remaining liquid may be taken up on sand, clay earth, floor, absorbent, or other absorbent material and sholveled into containers.

7. Handling and storage

7.1. Precautions for safe handling

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Avoid contact with: strong oxidizing agents, Strong alkalis, strong mineral acids.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0008052-41-3	Stoddard solvent	OSHA	TWA 500 ppm (2900 mg/m ³)
		ACGIH	TWA: 290 mg/m ³ STEL: 580 mg/m ³
		NIOSH	TWA 350 mg/m ³ C 1800 mg/m ³ [15-minute]
		Supplier	No Established Limit
0008052-42-4	Asphalt (petroleum)	OSHA	No Established Limit
		ACGIH	TWA: 0.5 mg/m ³ 2B
		NIOSH	Ca C 5 mg/m ³ [15-minute]
		Supplier	No Established Limit

8.2. Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Chemical splash goggles are advised. (consult your safety equipment supplier).

Skin

Wear resistant gloves such as: polyvinyl alcohol, viton. Other protective equipment: To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



9. Physical and chemical properties

Appearance	Black Liquid
Odor	Solvent-like Odor
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	260-320°F/127-160°C
Flash Point	105°F/41°C (ASTM D-92)
Evaporation rate (Ether = 1)	(X) Slower Than N-BUTYL ACETATE
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 0.9% Upper Explosive Limit: 6.0%
Vapor pressure (Pa)	Not Measured
Vapor Density	(X)Heavier Than Air ()Lighter than Air
Specific Gravity	.87
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Percent Solids (by weight)	50% (typical)
Percent Volatile (by weight)	50% (typical)
Percent Solids (by volume)	42% (typical)
Density (lbs/US gal)	7.5 (typical) @ 77°F

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



10.4. Conditions to avoid

No data available.

10.5. Incompatible materials

Avoid contact with: strong oxidizing agents, Strong alkalis, strong mineral acids.

10.6. Hazardous decomposition products

Burning may produce irritating Or toxic fumes. Carbon dioxide and carbon monoxide, various hydrocarbons, etc.

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Asphalt (petroleum) - (8052-42-4)	No data available	No data available	No data available	No data available	No data available
Stoddard solvent - (8052-41-3)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.50, Rat - Category: NA	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0008052-41-3	Stoddard solvent	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0008052-42-4	Asphalt (petroleum)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



IARC Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	1A	May Cause Cancer
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure	3	May cause respiratory irritation.
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Asphalt (petroleum) - (8052-42-4)	Not Available	Not Available	Not Available
Stoddard solvent - (8052-41-3)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1999	UN1999	UN1999
14.2. UN proper shipping name	UN1999,Tars,liquid	UN1999,Tars,liquid	UN1999,Tars,liquid
14.3. Transport hazard class(es)	DOT Hazard Class: 3	IMDG: 3 Sub Class: III	Air Class: 3
14.4. Packing group	III	III	III
14.5. Environmental hazards			
IMDG	No further information		
14.6. Special precautions for user	No further information		

15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



WHMIS Classification B2 D2B

US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (lbs):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Asphalt (petroleum)

Stoddard solvent

Pennsylvania RTK Substances (>1%):

Asphalt (petroleum)

Stoddard solvent

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

Safety Data Sheet

MAC BLACK

Revision Date: 03/17/2023



The information contained herein is furnished without warranty of any kind. The above information is believed to be correct but does not purport to be all inclusive and should be used only as a guide. Users should make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.

End of Document