

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



1. Identification

1.1. Product identifier

Product Identity	MACSEAL-REST
Alternate Names	MACREST Acrylic Restorer SOL-1004

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use	See Technical Data Sheet.
Application Method	See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name	Mac Coatings 1106 WALKER ROAD WINDSOR, ONTARIO N8Y 2N7
Customer Service: Mac Coatings	(519)-252-7275

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225	Highly flammable liquid and vapor.
Acute tox. oral 3; H301 + 311 + 331	Toxic if swallowed, in contact with skin or if inhaled.
Skin irrit. 2; H315	Causes Skin irritation.
Eye irrit. 2A; H319	Causes serious eye irritation.
STOT SE 3; H336	May cause drowsiness or dizziness.
Repr. 2; H361	Suspected of damaging fertility or the unborn child.
STOT RE 3; H373	May Cause damage to organs through prolonged or repeated exposure.
Asp. haz. 1; H304	May be fatal if swallowed and enters airways.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



DANGER

H225 Highly flammable liquid and vapor.

H301 + H311 + H331 Toxic if swallowed, in contact with skin or inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May Cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

[Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces and other ignition sources – No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breath dust/fumes/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection. Use only outdoors or in a well ventilated area.

[Response]:

P301 + 310 **IF SWALLOWED:** Immediately call a poison center or doctor/physician.

P302+352 **IF ON SKIN:** Wash with plenty of soap and water.

P303+361+353 **IF ON SKIN (or hair):** Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304 + 340 **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P304+312 **IF INHALED:** Call a POISON CENTER or doctor / physician if you feel unwell.

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



P305+351+338 **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P308 + 313 If exposed or concerned: Get medical advice/attention.

P331 Do NOT INDUCE VOMITING.

P332+313 If skin irritation occurs: Get medical advice / attention.

P337+313 If eye irritation persists: Get medical advice / attention.

P362 Take off contaminated clothing and wash before reuse.

P370 + 378 IN CASE OF FIRE: use Dry sand, dry chemical or alcohol resistant foam for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

2.3. Other Hazards

Vapors can accumulate in low areas. Vapors can form an explosive mixture with air.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Toluene CAS Number: 0000108-88-3	40-70	Flam. Liq. 2;H225 Repr. 2;H361 Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336	[1][2]
Methyl Ethyl Ketone CAS Number: 00000078-93-3	25-30	Flam. Liq. 2;H225 Eye irrit. 2A; H319 STOT SE 3;H336	[1][2]
Methanol CAS Number: 0000067-56-1	10-15	Flam. Liq. 2;H225 Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 3;H301 STOT SE 1;H370 (> 10%)	[1][2][3]
Ethylene glycol monobutyl ether CAS Number: 0000111-76-2	4-5	Acute Tox. 4;H332 Acute Tox. 4;H312 Acute Tox. 4;H302 Eye Irrit. 2;H319 Skin Irrit. 2;H315	[1][2]

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. Get Medical attention immediately.
Eyes	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash before reuse.
Ingestion	DO NOT INDUCE VOMITING. If conscious, rinse out mouth with water.

4.2. Most important symptoms and effects, both acute and delayed

Overview	Effects of overexposure: Acute: Eyes-may cause severe irritation, redness, tearing, blurred vision. Skin/skin absorption- Prolonged or repeated contact can cause moderate irritation. Defatting, dermatitis. Breathing-excessive inhalation of vapors can cause nasal and Respiratory irritation and central nervous system effects including: Dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. Swallowing-can cause gastrointestinal, irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. Exposure to solvent vapor concentrations in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.
Inhalation	May cause drowsiness or dizziness. May cause irritation of the mouth. Throat or esophagus.
Eyes	Causes eye irritation. May cause stinging/watering/redness/swelling.
Skin	Causes skin irritation.
Ingestion	Harmful if swallowed.

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical alcohol Foam, Water fog, Carbon Dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Burning may produce irritating Or toxic fumes. Carbon dioxide and carbon monoxide, various hydrocarbons, etc.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

Evacuate hazard area. Wear self-contained breathing apparatus with a full face piece

Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near container (even empty) because product (even just residue) can ignite explosively. All five gallon pails and large metal containers should be grounded and/or bonded when material is transferred.

ERG Guide No. ---

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways. Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Contain spillage and then collect with electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks, and open flames. Protect container from physical damage. Keep the container tightly closed when not in use. Store in a cool and well-Ventilated area.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000108-88-3	Toluene	OSHA	TWA (OSHA) 200 ppm C 300 ppm 500 ppm (10-minute maximum peak) STEL 150 ppm
		ACGIH	TWA: 20 ppm R
		NIOSH	TWA 100 ppm (375 mg/m3) ST 150 ppm (560 mg/m3)
		Supplier	No Established Limit
0000078-93-3	Methyl Ethyl Ketone(MEK)	OSHA	No Established Limit
		ACGIH	200 ppm STEL: 300 ppm
		NIOSH	No Established Limit
		Supplier	No Established Limit
0000067-56-1	Methanol	OSHA	TWA 200 ppm (260 mg/m3)
		ACGIH	TWA: 200 ppm STEL: 250 ppm Skin
		NIOSH	TWA 200 ppm (260 mg/m3) ST 250 ppm (325 mg/m3) [skin]
		Supplier	No Established Limit
0000111-76-2	Ethylene glycol monobutyl ether	OSHA	TWA 50 ppm (240 mg/m3) [skin]
		ACGIH	TWA: 20 ppm Revised 2003,
		NIOSH	TWA 5 ppm (24 mg/m3) [skin]
		Supplier	No Established Limit

8.2. Exposure controls

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



Respiratory	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicated this is necessary.
Eyes	Chemical goggles and face shield.
Skin	Chemical resistant, impervious gloves complying with an approved standard should be worn at all times. Coveralls, apron, and boots as necessary to minimize contact.
Engineering Controls	Use only in adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Liquid
Odor	Alcohol like
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	86.67 - 95°C
Flash Point	No data available
Evaporation rate (N-Butyl Acetate = 1)	(X) Faster Than N-BUTYL ACETATE
Flammability (solid, gas)	Flammable liquid
Upper/lower flammability or explosive limits	Lower Explosive Limit: NA Upper Explosive Limit: NA
Vapor pressure (hPa)	Not Measured
Vapor Density	(X)Heavier Than Air ()Lighter than Air
Specific Gravity	Not Measured
Solubility in Water	Immiscible
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
Percent Volatile (by volume)	90

9.2. Other information

No other relevant information.

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

Vapors may form an explosive mixture with air.

10.4. Conditions to avoid

High temperatures, flames, sparks

10.5. Incompatible materials

Avoid contact with: Strong acids and oxidizing materials.

10.6. Hazardous decomposition products

Smoke, carbon monoxide, carbon dioxide.

11. Toxicological information

Acute toxicity

Respiratory irritation

An inhalation hazard may only arise if product is used in aerosol conditions if heated up. The material is misted or if the vapors are generated from heating. Exposure may cause irritation of mucous membranes and upper respiratory tract.

Eye irritation

Causes serious eye irritation.

Skin Irritation

Causes mild skin irritation

Sensitization

Not expected to cause skin or respiratory sensitization.

Aspiration Hazard

If swallowed can be aspirated into lungs and cause chemical pneumonia, varying degrees of pulmonary injury or death.

If swallowed, do not induce vomiting.

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



Chronic Exposure

Vapor/aerosol concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects including death.

Prolonged or repeated direct exposure to the skin results in symptoms of irritation and redness, dermatitis or oil acne.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Toluene - (108-88-3)	636.00, Rat - Category: 4	8,400.00, Rabbit - Category: NA	No data available	No data available	No data available
Methyl Ethyl Ketone - (78-93-3)	2737, Rat - Category: NA	6480.00, Rabbit - Category: NA	32000, Mouse - Category: NA	No data	No data
Methanol - (67-56-1)	143.00, Human - Category: 3	No data available	No data available	No data available	64,000.00, Rat - Category: NA
Ethylene glycol monobutyl ether - (111-76-2)	1,414.00, Guinea Pig - Category: 4	1,200.00, Guinea Pig - Category: 4	173.00, Guinea Pig - Category: NA	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000108-88-3	Toluene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0000078-93-3	Methyl Ethyl Ketone(MEK)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000067-56-1	Methanol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000111-76-2	Ethylene glycol monobutyl ether	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



Classification	Category	Hazard Description
Acute toxicity (oral)	3	Toxic if swallowed.
Acute toxicity (dermal)	3	Toxic in contact with skin.
Acute toxicity (inhalation)	3	Toxic if inhaled.
Skin corrosion/irritation	2	Causes skin irritation.
Causes eye irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	2	Suspected of damaging fertility or the unborn child.
STOT-single exposure	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	1	May be fatal if swallowed and enters airways.

12. Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 Crustacia, mg/l	ErC50 algae, mg/l
Toluene - (108-88-3)	5.80, Oncorhynchus mykiss	19.60, Daphnia magna	Not Available
Methyl Ethyl Ketone - (78-93-3)	3130-3320, Pimephales promelas	>7060, Daphnia magna	No data available

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



Methanol - (67-56-1)	100.00, Pimephales promelas	10,000.00, Daphnia magna	16.912 (96 hr), Ulva pertusa
Ethylene glycol monobutyl ether - (111-76-2)	220.00, Fish (Piscis)	1,000.00, Daphnia magna	Not Available

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

Toxic to aquatic life.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1263	UN1263	UN1263
14.2. UN proper shipping name	UN1263	1263	1263
14.3. Transport hazard class(es)	DOT Hazard Class: 3	IMDG: 3 Sub Class: Not Applicable	Air Class: 3
14.4. Packing group	III	II	II
14.5. Environmental hazards			
IMDG	No further information		
14.6. Special precautions for user	No further information		

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

US EPA Tier II Hazards

Fire: Yes
Sudden Release of Pressure: No
Reactive: No
Immediate (Acute): Yes
Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs (lbs):

Toluene
Methanol
Methyl Ethyl Ketone

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Toluene
2-Butoxyethanol

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

Toluene.
Methanol

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Toluene
Methyl Ethyl Ketone
Methanol
2-Butoxyethanol

Pennsylvania RTK Substances (>1%):

Safety Data Sheet

MACSEAL-REST

Revision Date: 06/15/2023



Toluene

Methyl Ethyl Ketone

Methanol

2-Butoxyethanol

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The information contained herein is furnished without warranty of any kind. The above information is believed to be correct but does not purport to be all inclusive and should be used only as a guide. Users should make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.

End of Document