Safety Data Sheet
Methylene Chloride

SDS Revision Date: 01/18/2023

1. Identification

1.1. Product identifier

Product Identity	SOL-1049(Methylene Chloride)
Alternate Names	Dichloromethane

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use	See Technical Data Sheet.
Application Method	See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name	Mac Coatings 1106 WALKER ROAD WINDSOR, ONTARIO N8Y 2N7
Customer Service: Mac Coatings	(519)-252-7275

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Skin irrit. 2; H315	Causes Skin irritation.
Eye irrit. 2A; H319	Causes serious eye irritation.
STOT SE 3; H336	May cause drowsiness or dizziness.
Carc. 2; H351	Suspected of causing cancer.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

Warning

H315 Causes skin irritation.
H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.

[Prevention]:
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/fumes/gas/mist/vapours/spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well ventilated area.
P280 Wear protective gloves / eye protection / face protection. Use only outdoors or in a well ventilated area.
[Response]:
P302+352 **IF ON SKIN:** Wash with plenty of soap and water.
P304 + 340 **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338 **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
P312 If exposed or concerned: Get medical advice/attention.
P332+313 If skin irritation occurs: Get medical advice / attention.
P362+P364 Take off contaminated clothing and wash before reuse.
P337+313 If eye irritation persists: Get medical advice / attention.
[Storage]:
P403+233 Store in a well ventilated place. Keep container tightly closed.
P405 Store locked up.
[Disposal]:
P501 Dispose of contents / container in accordance with local / national regulations.

2.3. Other Hazards
Vapors can accumulate in low areas. Vapors can form an explosive mixture with air.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Dichloromethane **CAS Number: 0000075-09-2**	**100**	**Acute tox. Oral 4; H302** **Skin irrit. 2; H315** **Eye irrit. 2A; H319** **STOT SE 3; H335** **STOT SE 3;H336**	**[1][2]**

		STOT SE 1;H370 **Carc. 2;H351**	

[1] Substance classified with a health or environmental hazard.
[2] Substance with a workplace exposure limit.
[3] PBT-substance or vPvB-substance.
*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. Get Medical attention immediately.

Eyes Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash before reuse.

Ingestion DO NOT INDUCE VOMITING. If conscious, rinse out mouth with water.

4.2. Most important symptoms and effects, both acute and delayed

Overview Effects of overexposure:
Acute: Eyes-may cause severe irritation, redness, tearing, blurred vision.
Skin/skin absorption- Prolonged or repeated contact can cause moderate irritation. Defatting, dermatitis.
Breathing-excessive inhalation of vapors can cause nasal and Respiratory irritation and central nervous system effects including: Dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.
Swallowing-can cause gastrointestinal, irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
Exposure to solvent vapor concentrations in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Inhalation May cause drowsiness or dizziness. May cause irritation of the mouth. Throat or esophagus.

Eyes Causes eye irritation. May cause stinging/watering/redness/swelling.

Skin Causes skin irritation.

Ingestion Harmful if swallowed.

5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical alcohol Foam, Water fog, Carbon Dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Burning may produce irritating Or toxic fumes. Carbon dioxide and carbon monoxide, various hydrocarbons, etc.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

Evacuate hazard area. Wear self-contained breathing apparatus with a full face piece
Vapors are heavier than air and may travel along the ground or may be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near container (even empty) because product (even just residue) can ignite explosively. All five gallon pails and large metal containers should be grounded and/or bonded when material is transferred.

ERG Guide No. ---

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways. Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Contain spillage and then collect with electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks, and open flames. Protect container from physical damage. Keep the container tightly closed when not in use. Store in a cool and well-Ventilated area.
See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000075-09-2	Dichloromethane	OSHA	[1910.1052] TWA 25 ppm ST 125 ppm
		ACGIH	TWA: 25 ppm 2B
		NIOSH	Ca
		Supplier	No Established Limit

8.2. Exposure controls

Respiratory	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicated this is necessary.
Eyes	Chemical goggles and face shield.
Skin	Chemical resistant, impervious gloves complying with an approved standard should be worn at all times. Coveralls, apron, and boots as necessary to minimize contact.
Engineering Controls	Use only in adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Liquid
Odor	Characteristic
Odor threshold	Not determined
pH	Not Measured
Melting point / freezing point	-97°C/-143°F
Initial boiling point and boiling range	39.8 - 40°C
Flash Point	No data available
Evaporation rate (N-Butyl Acetate = 1)	(X) Faster Than N-BUTYL ACETATE
Flammability (solid, gas)	No Applicable
Upper/lower flammability or explosive limits	**Lower Explosive Limit:** 17% **Upper Explosive Limit:** 19%
Vapor pressure (hPa)	470.9
Vapor Density	(X)Heavier Than Air ( )Lighter than Air
Specific Gravity	1.325
Solubility in Water	Slightly soluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	556°C
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
Percent Volatile (by volume)	100

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

Vapors may form an explosive mixture with air.

10.4. Conditions to avoid

High temperatures, flames, sparks

10.5. Incompatible materials

Avoid contact with: Strong acids and oxidizing materials.

10.6. Hazardous decomposition products

Smoke, carbon monoxide, carbon dioxide.

11. Toxicological information

Acute toxicity

Respiratory irritation
An inhalation hazard may only arise if product is used in aerosol conditions if heated up. The material is misted or if the vapors are generated from heating. Exposure may cause irritation of mucous membranes and upper respiratory tract.

Eye irritation
Causes serious eye irritation.

Skin Irritation
Causes mild skin irritation

Sensitization
Not expected to cause skin or respiratory sensitization.

Aspiration Hazard
If swallowed can be aspirated into lungs and cause chemical pneumonia, varying degrees of pulmonary injury or death.
If swallowed, do not induce vomiting.

Chronic Exposure

Vapor/aerosol concentrations above recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects including death.
Prolonged or repeated direct exposure to the skin results in symptoms of irritation and redness, dermatitis or oil acne.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Dichloromethane - (75-09-2)	1,600.00, Rat - Category: 4	No data available	52.00, Rat - Category: NA	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000075-09-2	Dichloromethane	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: Yes
		IARC	Group 1: No; Group 2a: Yes; Group 2b: No; Group 3: No; Group 4: No;

Classification	Category	Hazard Description
Acute toxicity (oral)	4	Harmful if swallowed.
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Causes eye irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	2	Suspected of causing cancer.
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause respiratory irritation.
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-Single exposure	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 Crustacia, mg/l	ErC50 algae, mg/l
Dichloromethane - (75-09-2)	99.00, Pimephales promelas	1,250.00, Daphnia magna	242.00 (72 hr), Chlamydomonas reinhardtii

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1593	UN1593	UN1593
14.2. UN proper shipping name	Dichloromethane	Dichloromethane	Dichloromethane
14.3. Transport hazard class(es)	**DOT Hazard Class:** 3	**IMDG:** 3 **Sub Class:** Not Applicable	**Air Class:** 3
14.4. Packing group	III	III	III

14.5. Environmental hazards

IMDG No further information

14.6. Special precautions for user

No further information

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

US EPA Tier II Hazards

Fire: Yes
Sudden Release of Pressure: No
Reactive: No
Immediate (Acute): Yes
Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs (lbs):
Dichloromethane

EPCRA 302 Extremely Hazardous:
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:
Dichloromethane

Proposition 65 - Carcinogens (>0.0%):
Dichloromethane

Proposition 65 - Developmental Toxins (>0.0%):
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):
To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Dichloromethane

Pennsylvania RTK Substances (>1%):

Dichloromethane

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our

products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 Suspected of causing cancer.

H370 Causes damage to organs.

H351 Suspected of causing cancer.

The information contained herein is furnished without warranty of any kind. The above information is believed to be correct but does not purport to be all inclusive and should be used only as a guide. Users should make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.

End of Document